

## HLCV.EX27352 - STRAINERS, PIPELINE

## Strainers, Pipeline

See General Information for Strainers, Pipeline

**CLA-VAL CO**

EX27352

PO BOX 1325

NEWPORT BEACH, CA 92659-0325 USA

**Strainers, Y- type, 2, 2.5, 3, 4, 5, 6, 8, 10 and 12 in. sizes, for rated working pressure of 200 psi or 1380 kPa, Model(s)**  
GC70-200, GF70-200, GG70-200

**Strainers, Y- type, 2, 2.5, 3, 4, 5, 6, 8, 10 and 12 in. sizes, for rated working pressure of 250 psi or 1725 kPa, Model(s)**  
GC70-250, GF70-250, GG70-250

**Strainers, Y- type, 2, 2.5, 3, 4, 5, 6, 8, 10 and 12 in. sizes, for rated working pressure of 300 psi or 2070 kPa, Model(s)**  
GC70-300, GF70-300, GG70-300

NOTE - Loss of head will approximate 7.22 psi (49.78 kpa) for the 2 in. size at 157.63 GPM, 5.89 psi (40.61 kpa) for the 2-1/2 in. size at 224.86 GPM, 8.24 psi (56.81 kpa) for the 3 in. size at 347.53 GPM, 5.88 psi (40.54 kpa) for the 4 in. size at 598.54 GPM, 7.63 psi (52.61 kpa) for the 5 in. size at 940.7 GPM, 4.82 psi (33.23 kpa) for the 6 in. size at 1358.85 GPM, 5.83 psi (40.20 kpa) for the 8 in. size at 2405.84 GPM, 7.25 psi (49.99 kpa) for the 10 in. size at 3795.17 GPM and 5.73 psi (39.51 kpa) for the 12 in. size at 5442.11 GPM.

Last Updated on 2016-12-14

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过 UL 认证，并满足 UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明：“© 2019 UL LLC”